

AudioCodes Teams C455HD IP-Phone PoE GbE black

Brand : AudioCodes

Product code: TEAMS-C455HD

Product name : Teams C455HD IP-Phone PoE GbE black

- Native support for Microsoft Teams
- Graphical 5" color TFT screen (1280 x 720) with multi-lingual support
- Full Duplex Speakerphone
- Touch screen user interface enabling up to 8 programmable keys
- 8 line, 8 concurrent calls per line
- PoE or external power supply

Teams C455HD IP-Phone PoE GbE black

AudioCodes Teams C455HD IP-Phone PoE GbE black:

The AudioCodes Microsoft Teams-native C455HD IP phone is a feature-rich, executive high-end business phone, packed with the latest technology for delivering a seamless Microsoft Teams experience every time. The C455HD is equipped with a large and intuitive 5" color touch screen for exceptional ease-of-use, while stunning HD sound quality ensures that every conversation is productive – and then some. This device is also available as the C455HD-DBW, complete with a 5" color touch expansion module that really brings your Microsoft Teams meetings to life, as well as dual band Wi-Fi and Bluetooth for wireless headsets.



Design		Network	
Product type *	IP Phone	Ethernet LAN interface type	Gigabit Ethernet
Handset type	Wired handset	Ethernet LAN data rates	10,100,1000 Mbit/s
Product colour *	Black	Wi-Fi *	✗
Wall mountable	✓	Bluetooth *	✗
Performance		Supported network protocols	IPv4, TCP, UDP, ICMP, ARP, RTP, SRTP, RTCP-XR, 802.1x, IP/DHCP IP, IEEE 802.1p/Q, QoS/ToS, HTTP/HTTPS/DHCP, NTP, FTP/TFTP, CDP/LLDP VLAN, LDAP
Operating system installed	Android	Quality of Service (QoS) support	✓
Operating system version	9	Security algorithms	HTTPS, SRTP, SSL/TLS
Dual-Tone Multi-Frequency (DTMF) modes	SIP info	Networking standards	IEEE 802.1Q, IEEE 802.1p, IEEE 802.1x, IEEE 802.3af
Phone features		Ports & interfaces	
Lines quantity *	8 lines	USB 2.0 ports quantity	2
Answering machine	✓	Ethernet LAN (RJ-45) ports	2
Call waiting	✓	RJ-9 ports quantity	1
Speed dialling	✓	DC-in jack	✓
Call hold	✓	WAN connection type	RJ-45
Call forwarding	✓	Cable lock slot	✓
Conference call	✓	Certificates	
Redialing	✓	Sustainability compliance	✓
Do not disturb function	✓	Compliance certificates	CE, Federal Communications Commission (FCC)
Caller ID *	✓	Power	
Call park	✓	Power over Ethernet (PoE) *	✓
Call pick up	✓	AC adapter input voltage	100 - 240 V
Full duplex	✓	AC adapter output voltage	12 V
Call transfer	✓	AC adapter output current	2 A
Message-waiting indicator (MWI)	✓	Operational conditions	
Management features		Operating temperature (T-T)	0 - 40 °C
Integrated voicemail	✓	Storage temperature (T-T)	-20 - 70 °C
Volume control	Buttons		
Number of programmable keys	8		
Firmware upgradeable	✓		

Display		Weight & dimensions	
Display	TFT	Width	236 mm
Display diagonal	12.7 cm (5")	Depth	200 mm
Display resolution	1280 x 720 pixels	Height	165.9 mm
Touchscreen *	✓	Weight	988 g
Audio		Height (min)	17 cm
Speakerphone *	✓	Height (max)	19.5 cm
Microphone mute	✓	Package width	280 mm
Voice codecs	G.711Mu, G.711a, G.722, G.729A, G.729B, OPUS	Package depth	245 mm
Echo cancellation	✓	Package height	110 mm
Voice activity detection	✓	Package weight	1.55 kg
Adaptive jitter buffers	✓	Packaging content	
Packet loss concealment (PLC)	✓	Number of handles included *	1 pc(s)
Network		Manual	✓
Ethernet LAN *	✓	Cables included	LAN (RJ-45)
		Logistics data	
		Master (outer) case gross weight	14.5 kg
		Master (outer) case length	467 mm
		Master (outer) case width	579 mm
		Master (outer) case height	291 mm



7613081108027



5715063673065

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.